

ID07 UNDERWATER IMPACT DRILL

STANLEY®



SPECIFICATIONS

Capacity	½" / 12.7 mm Square Drive
Performance	Torque 500 ft lbs / 675 Nm
Flow Range	4-12 gpm / 15-45 lpm
Working Pressure	750-2000 psi / 50-140 bar
Full Relief Setting	2250 psi / 155 bar
Weight	7.2 lbs / 3.3 kg
Length	10" / 25.4 cm
Width	4¼" / 10.8 cm
Hydraulic Ports	-8 SAE O-ring
Connect Size and Type	¾" Male Pipe Adapter
Couplers	(See Ordering Information)
Hose Whips	(See Ordering Information)

FEATURES

- Integral Stanley Hyrevz gear motor produces high torque
- Stainless Steel spools and fasteners
- Forward-Reverse with variable speed
- 500 ft lbs/675 Nm of impact torque
- Oversized trigger with guard for operator comfort
- Wiper seals on reversing and trigger spool
- Built in reverse check valve ensures long seal life
- Plastisol handle for comfortable ergonomic grip
- Forward position of handle provides better balance
- Open Center/Closed Center-Dual Spool Feature
- Cast-in lifting eye



The Stanley **ID07** Impact/Drill is two hydraulic underwater tools in one - an impact wrench and a wood drill. The ½" square drive impact wrench delivers torque up to 500 ft lbs and can tighten and loosen nuts and bolts and drive lag screws. Use the **ID07** with the 05079 Adapter and wood boring bits for drilling in timbers up to 1½" diameter holes with no reactive torque to the diver. Trigger guard and hi-visibility yellow paint is standard.

ID07 UNDERWATER IMPACT DRILL

STANLEY

ORDERING INFORMATION

PART NUMBER

ID07920	Impact/Drill, Underwater, ½" Square Drive, less couplers
ID0792001	Impact/Drill, Underwater, CE, ½" Square Drive, w/hose whips and couplers

ACCESSORIES

03971	Flush-Face Coupling Set, ⅜" NPT
03974	Flush-Face Coupling Set, ½" NPT
31848	Dual Hose, 50' x ½", with couplers
31972	Dual Hose, 25' x ½", with couplers
58633	Twinned Hose, 25' x ½", with couplers
58634	Twinned Hose, 50' x ½", with couplers

When hydraulic hose exceeds 100' (30.4 m) in length, increase I.D. of both pressure and return hose. For more information, consult Stanley Hydraulic Tools.

Wood Boring Bits have 7/16" Quick Change, Hex Shank Requires Part # 05079 Adaptor for use with ID07 U/W Impact/Drill

05079	Adaptor ½" female sq. dr. x 7/16" QC Hex
27850	Wood Bit: 9/16" dia. x 8" x 12" OAL
27851	Wood Bit: 1 1/16" dia. x 8" x 12" OAL
27852	Wood Bit: 1 3/16" dia. x 8" x 12" OAL
27853	Wood Bit: 1 5/16" dia. x 8" x 12" OAL
27854	Wood Bit: 1 7/16" dia. x 8" x 12" OAL
27855	Wood Bit: 9/16" dia. x 12" x 16" OAL
27856	Wood Bit: 1 1/16" dia. x 12" x 16" OAL
27857	Wood Bit: 1 3/16" dia. x 12" x 16" OAL
27858	Wood Bit: 1 5/16" dia. x 12" x 16" OAL
27859	Wood Bit: 1 7/16" dia. x 12" x 16" OAL
27860	Wood Bit: 9/16" dia. x 18" x 22" OAL
27861	Wood Bit: 1 1/16" dia. x 18" x 22" OAL
27862	Wood Bit: 1 3/16" dia. x 18" x 22" OAL
27863	Wood Bit: 1 5/16" dia. x 18" x 22" OAL
27864	Wood Bit: 1 7/16" dia. x 18" x 22" OAL



Distributor of Stanley:
SCANTEK Sp. z o.o.
81-581 Gdynia, ul. Nowodworcowa 17
Tel/fax: +48 58 620 83 60 / 58 620 03 04
mob. +48 501 734 143 / 507 11 0873
www.scantek.pl, e-mail: info@scantek.pl

STANLEY

Stanley Hydraulic Tools | 3810 SE Naef Road | Milwaukie, Oregon 97267 | +01.503.659.5660 | 800.972.2647 | www.stanleyhydraulic.com