

LW 160 E1



The user-friendly LW 160 E1 with electric drive is ideal for mobile applications or occasional filling operations.

It comes wired with power cable, plug and phase selector.

The model differs in E and E 1 (E- three phase / E1-single phase version).

Specifications

- » Electro Motor (Standard: 230V, single phase, 50Hz)
- » Power cable with plug and phase selector
- » Start/Stop Switch
- » Stainless steel frame
- » Manual condensate drain
- » Pressure maintaining and non return valve
- » 1x Filling hose c/w filling valve and pressure gauge
- » Intermediate coolers
- » Oil- / Water separators after 2nd and 3rd stage
- » Safety valves after each stage
- » Filling pressure to your choice (200 or 300 bar)
- » Connections to your choice
(DIN 200 bar or 300 bar, CGA 200 bar or 300 bar and INT)
- » Breathing air purification an accordance to EN 12021

Options

- » Additional filling hose c/w filling valve
- » Automatic condensate drain
- » Automatic stop at final pressure c/w hour counter
- » Switch over device for 200 or 300 bar
- » Motor protection switch
- » Special voltages / frequencies on request
- » Conversion set: Petrol-/electro version



Technical Data

LW 160 E1	
Type:	Air cooled piston compressor
Capacity [litre/min] / [Nm ³ /h] / [cfm]:	160 / 9.6 / 5.6
Max. Pressure [bar]:	330
RPM [1/min]:	1450
No of cylinders / No of stages:	3 / 3
Prime mover type:	E-Motor / 230V / single phase / 50Hz
Drive power [kW] / [HP]:	3.7 / 5.0
Cooling air requirement [Nm ³ /h]:	1200
Lubrication type:	Splash oil
Oil capacity [litre]:	0.8
Operating temperature [°C]:	+5°C to +45°C
Filter capacity [m ³ at +20°C] ¹⁾ :	180 (at +20°C / approx. 19 h)
Dimensions L x W x H [cm]:	78 x 42 x 56
Weight [kg]:	90
Noise level [dB]:	84 (measured at 1 m)

¹⁾ In accordance with EN 12021

Official distributor of Lenhardt and Wagner:



SCANTEK Sp. z o.o.
81-581 Gdynia, ul. Nowodworcowa 17
Tel/fax: +48 58 620 83 60 / 58 620 03 04
mob. +48 501 734 143 / 507 11 0873
www.scantek.pl, e-mail: info@scantek.pl