

LW 190 B



The user-friendly compressor with 4-stroke power in a compact design is a popular alternative for expeditions and safaris.

The LW 190 B is portable and therefore ideal for mobile applications or occasional filling operations.

Specifications

- » 4 stroke drive motor c/w pull start and auto cut off at low oil level
- » Steel frame c/w carrying handles
- » Manual condensate drain
- » Inclusive air intake pipe
- » Pressure maintaining and non return valve
- » 1x Filling hose c/w filling valve and pressure gauge
- » Intermediate coolers
- » Stainless steel pipes
- » Oil- / Water separators after 2nd and 3rd stage
- » Safety valves after each stage
- » Filling pressure to your choice (200 or 300 bar)
- » Connections to your choice
(DIN 200 bar or 300 bar, CGA 200 bar or 300 bar and INT)
- » Breathing air purification an accordance to EN 12021

Options

- » Additional filling hose c/w filling valve
- » Automatic stop at final pressure
- » Switch over device for 200 and 300 bar
- » Hour counter
- » Conversion set: Petrol-/electro version



Technical Data

LW 190 B	
Type:	Air cooled piston compressor
Capacity [litre/min] / [Nm³/h] / [cfm]:	190 / 11.4 / 6.7
Max. Pressure [bar]:	330
RPM [1/min]:	1900
No of cylinders / No of stages:	3 / 3
Prime mover type:	4 stroke drive motor (pull start)
Drive power [kW] / [HP]:	6.0 / 9.0
Cooling air requirement [Nm³/h]:	1800
Lubrication type:	Splash oil
Oil capacity [litre]:	0.8
Operating temperature [°C]:	+5°C to +45°C
Filter capacity [m³ at +20°C] ¹⁾ :	150 (at +20°C / approx. 13 h)
Dimensions L x W x H [cm]:	92 x 43 x 57
Weight [kg]:	94
Noise level [dB]:	93 (measured at 1 m)

¹⁾ In accordance with EN 12021

Official distributor of Lenhardt and Wagner:



SCANTEK Sp. z o.o.
81-581 Gdynia, ul. Nowodworcowa 17
Tel/fax: +48 58 620 83 60 / 58 620 03 04
mob. +48 501 734 143 / 507 11 0873
www.scantek.pl, e-mail: info@scantek.pl