

**NEW!**



# LW 320 E MC

The new MC Series from L&W has been created for dive centers, ships, boats and places with limited space. These are suitable for continuous operation and guarantee low maintenance costs due to long service intervals. Depending on the motor size they are fully equipped with either direct- or star /delta start systems. A super lightweight aluminum frame enables mobile applications, combined with very high filling capacity. The robust and powerful compressor block also allows being used at fully automatic stationary plants.



Figure with options



**NEW!**

# LW 320 E MC

**Compressors**

## Specifications

- » Electro motor (Standard: 400V, 3 phase, 50Hz)
- » Painted lightweight aluminium frame in RAL 7001
- » Hour counter
- » Start/ Stop switch or star/delta start system
- » Emergency stop switch
- » Manual condensate drain
- » 1 x Filling hose c/w filling valve
- » Pressure maintaining and non return valve
- » All pistons c/w steel piston rings
- » Low pressure oil pump
- » Oil filter with bypass
- » Oil- / Water separators after 2nd and 3rd stage
- » Safety valves after each stage
- » 3 x concentric suction/pressure valves
- » Filling pressure to your choice (200 or 300 bar)
- » Connections to your choice  
(DIN 200 bar or 300 bar, CGA 200 bar or 300 bar and INT)
- » Breathing air purification in accordance to EN 12021



Control panel c/w options



Filling pressure gauge c/w options

## Options

- » Automatic condensate drain incl. collecting tank
- » Automatic stop at final pressure
- » Additional filling hoses c/w filling valves
- » Auto start system
- » Switch over device 200/300 bar
- » 200 and 300 bar parallel filling pressures
- » Oil pressure gauge
- » Oil pressure monitoring c/w auto shut down
- » Intermediate pressure gauges
- » Cylinder head temperature monitoring with auto shut down
- » Puracon filter monitoring (Auto shut down also available)
- » Phase monitoring c/w shut down at wrong direction of rotation
- » 1.7 l filter system (Filter capacity 900 m<sup>3</sup> at +20°C)
- » Remote control box
- » Additional high pressure outlet
- » Wheel set
- » Power cable and plug
- » Special voltages / frequencies on request

## Technical Data

LW 320 E MC	
Type:	Air cooled piston compressor
Capacity [litre/min] / [Nm <sup>3</sup> /h] / [cfm]:	320 / 19.2 / 11.3
Max. Pressure [bar]:	350
RPM [1/min]:	1300
No of cylinders / No of stages:	3 / 3
Prime mover type:	E-Motor / 400V / 3 Phase / 50-60 Hz
Drive power [kW] / [HP]:	7.5 / 10.0
Cooling air requirement [Nm <sup>3</sup> /h]:	2250
Lubrication type:	Oil pump + Splash oil
Oil capacity [litre]:	approx. 2.0
Oil pressure [bar]:	2.5 - 4.0 (± 0.5)
Operating temperature [°C]:	+5°C to +45°C
Filter capacity [m <sup>3</sup> at +20°C] <sup>1)</sup> :	108 (at +20°C)
Dimensions L x W x H [mm]:	1280 x 495 x 825
Weight [kg]:	155 - 175
Noise level [dB]:	82 (measured at 1 m)

<sup>1)</sup> In accordance with EN 12021

Official distributor of Lenhardt and Wagner:



SCANTEK Sp. z o.o.  
 81-581 Gdynia, ul. Nowodworcowa 17  
 Tel/fax: +48 58 620 83 60 / 58 620 03 04  
 mob. +48 501 734 143 / 507 11 0873  
 www.scantek.pl, e-mail: info@scantek.pl