

# LW 720 E



The industrial compressor LW 720 E is suitable for breathing air applications and for large capacities. Low speed ensures continuous operation for long service intervals and reduced maintenance costs. The 4-stage compressor block is mounted on a painted steel panel and is designed for maximum operating pressure of 420 bar. The compressor unit comes fully wired with star/delta start system and includes 2x 2.3 litre breathing air filter console for wall mounting.



LW 720 E with optional ECC control

# LW 720 E



## Specifications

- » Electro motor (Standard: 400V, 3 phase, 50Hz)
- » Painted steel frame (RAL 6026)
- » Painted steel fan guard (RAL 7004)
- » Automatic condensate drain
- » Automatic stop at final pressure
- » Inclusive a remote control box for wall mounting
- » Main-, Start/Stop- and condensate test buttons, as well as emergency stop switch
- » Hour counter
- » Oil pressure gauge
- » Intermediate pressure gauges
- » Oil pressure monitoring c/w auto shut down
- » High pressure outlet 10 l
- » Motor protection switch
- » Pressure maintaining and non return valve
- » All pistons c/w steel piston rings
- » Low pressure oil pump and filter
- » Oil- / Water separators in stainless steel
- » Safety valves after each stage
- » 4 concentric suction/pressure valves
- » Filling pressure of your choice (200 or 300 bar)
- » Inclusive 2 x 2.3 l filter console for wall mounting
- » Breathing air purification in accordance to EN 12021

## Options

- » Auto start system
- » Oil temperature display with auto shut down
- » Cylinder head temperature monitoring with auto shut down
- » Puracon filter monitoring (Auto shut down also available)
- » ECC control in remote control box
- » Power cable and plug
- » Block heating device
- » 420 bar Version
- » Special voltages / frequencies on request

## Technical Data

LW 720 E	
Type:	Air cooled piston compressor
Capacity [litre/min] / [Nm <sup>3</sup> /h] / [cfm]:	720 / 43.2 / 25.4
Max. Pressure [bar]:	350 / 420
RPM [1/min]:	1100
No of cylinders / No of stages:	4 / 4
Prime mover type:	E-Motor / 400V / 3 Phase / 50 Hz
Drive power [kW] / [HP]:	18.5 / 25.0
Cooling air requirement [Nm <sup>3</sup> /h]:	5550
Lubrication type:	Oil pump + Splash oil
Oil capacity [litre]:	4.0
Oil pressure [bar]:	4.0 (+/- 0.5)
Operating temperature [°C]:	+5°C to +45°C
Filter capacity [m <sup>3</sup> at +20°C] <sup>1)</sup> :	2400 (at +20°C / approx. 56 h)
Dimensions L x W x H [cm]:	167 x 77 x 117
Weight [kg]:	600
Noise level [dB]:	88 (measured at 1 m)

<sup>1)</sup> In accordance with EN 12021

Official distributor of Lenhardt and Wagner:



SCANTEK Sp. z o.o.  
81-581 Gdynia, ul. Nowodworcowa 17  
Tel/fax:+48 58 620 83 60 / 58 620 03 04  
mob. +48 501 734 143 / 507 11 0873  
www.scantek.pl, e-mail: info@scantek.pl