



THE WORLDWIDE
DIVING STANDARD

VIKING™ HAZTECH



VIKING HAZTECH with latex neck seal
(inset shows a black VIKING HAZTECH
with Surveyor latex hood).

VIKING™ HAZTECH is a lightweight robust suit for diving in hazardous water conditions, particularly where there may be a danger of heat exhaustion in warm water or hot climatic conditions. Now available in all black with non-magnetic zipper for military and law enforcement operations.

- Lightweight and robust material
- High frequency welded seams for maximum strength and safety
- Ideal for warm water and/or warm climate diving
- Tested for flex cracking after > 200 flexes down to -40° C
- Easy clean exterior surface
- Suitable for contaminated water diving operations

SUIT MATERIAL

TPU (thermoplastic polyurethane) outer layer in red or black, single coated onto a black knitted nylon fabric.
Total material weight is approximately 480 ± 40 g/m².

SEAMS

External seams are high frequency welded for maximum strength and safety. A seam tape is heat applied to the inside of the seams.

COLOUR

Red with black reinforcements or all black.

SIZE RANGE

- VIKING Regular: 00/SML, 01/MED, 02/LGE, 03/EXL, 04/XXL
- VIKING Wide: 00/SML, 01/MED, 02/LGE, 03/EXL, 04/XXL
- VIKING Double Wide: 00/SML, 01/MED, 02/LGE, 03/EXL, 04/XXL

See the VIKING size chart for detailed size measurements along with boot sizing.



THE WORLDWIDE
DIVING STANDARD

VIKING™ HAZTECH



High frequency welded seam

REINFORCEMENTS

Black reinforcements are welded onto shoulders, elbows and knees.

ZIPPER

A 90 cm long medium duty PU zipper is HF welded across the shoulders. All black suits are fitted with a non-mag zipper as standard.

VALVES

Standard configuration includes:

- Push protected inlet valve, positioned centrally on the chest
- Hose: CEJN fitting, 80 cm long
- VIKING X2 exhaust valve with double check valves

NECK SEAL

The VIKING HAZTECH is fitted with a Surveyor latex neck seal as standard. Option: VIKING Quick Neck collar system, which allows for quick changing of broken seals.

Note: Quick Neck collars are NOT recommended for contaminated water diving operations.

HOOD OPTIONS

VIKING HAZTECH suits may be fitted with a wide range of hood options as follows: Surveyor latex hood + thermal inner hood, Smoothskin hood (these are not recommended for contaminants other than biological), Magnum or Turbo HDS hood.

YOKES

A full range of rubber yokes are available in NITECS material: SL 27/37, Desco, AH3, Genesis, Gorski, Deepsea and Dräger.

CUFFS

Latex PRO cuffs are fitted as standard. Alternatively the suit can be fitted with a HDS rubber cuff ring system or the VIKING Bayonet Ring System. Both systems make the use of latex gloves or mittens possible.

FOOTWEAR

Rubber coated 5 mm neoprene boots are fitted as standard. Alternative boot options are available.

INCLUDED WITH EACH DELIVERY

Each suit comes supplied with suspenders, carry bag, user manual, repair kit and zip care materials.

CERTIFICATION & APPROVALS

- EN 14225-2:2005
- BIO approval
- HZ chemical approval

Official distributor of Ansell Protective Solutions:



SCANTEK Sp. z o.o.
81-581 Gdynia, ul. Nowodworcowa 17
Tel/fax:+48 58 620 83 60 / 58 620 03 04
kom. +48 501 734 143 / 507 11 0873
www.scantek.pl, e-mail: info@scantek.pl