



**THE WORLDWIDE  
DIVING STANDARD**

## VIKING™ PRO



VIKING PRO with latex neck seal (inset shows a black VIKING PRO with Surveyor hood).

**The VIKING PRO is Ansell's biggest selling dry suit worldwide. Designed for flexibility and comfort in a wide range of applications. Vulcanized seams allow for peace of mind when diving under all situations.**

- Internal stitched and taped seams
- External vulcanized seams
- Easy to clean exterior when contaminated
- Easy to repair in the field to minimize downtime
- Flexible and comfortable

### SUIT MATERIAL

Blend of natural and synthetic rubbers (NR/EPDM), on a 2-way stretch knitted polyester lining.  
Total material weight is 1050 g/m<sup>2</sup> ± 100 g/m<sup>2</sup>.

### SEAMS

Internal seams are stitched together with an elastic tape for security. External seams are vulcanized with a 25 mm rubber tape. Vulcanizing is a chemical bonding process, ensuring watertight seams.

### COLOR

Red with black reinforcements, or all black.

### SIZE RANGE

- VIKING Regular: 00/SML, 01/MED, 02/LGE, 03/EXL, 04/XXL, 05/XXXL
- VIKING Wide: 00/SML, 01/MED, 02/LGE, 03/EXL, 04/XXL
- VIKING Double Wide: 00/SML, 01/MED, 02/LGE, 03/EXL, 04/XXL

See the VIKING size chart for detailed size measurements along with boot sizing.

Vulcanized rubber suits are not custom built due to dependency of aluminum mannequins for vulcanization. Extension and shortening of arm and leg length is possible and offered separately.



THE WORLDWIDE  
DIVING STANDARD

# VIKING™ PRO

ANSELL 1507 (A4)



Internal stitched seam

## REINFORCEMENTS

Additional layers of anti-slip textured rubber are applied to areas at risk of wear. The shoulders and zipper are reinforced. The trouser rear reinforcement extends around the thigh and across to the front of the legs, and down over the boots.

## ZIPPER

A 90 cm long Heavy Duty zipper is placed across the shoulders. The zipper is gas and watertight. Black suits are supplied with a non-mag zipper.

## VALVES

Standard configuration includes the following mounted on rubber backing discs:

- Push protected inlet valve, positioned centrally on the chest
- Hose: CEJN fitting, 80 cm long
- VIKING X2 exhaust valve, placed on the upper left arm

## NECK SEAL

The VIKING PRO is fitted with a Surveyor latex neck seal as standard. Option: VIKING Quick Neck collar system, which allows for quick changing of broken seals.

## HOOD OPTIONS

VIKING PRO suits may be fitted with a wide range of hood options as follows: Surveyor latex hood + thermal inner hood, Nautic neoprene hood with smooth face seal, Smoothskin hood, Turbo black rubber hood or Magnum black rubber hood.

## CUFFS

Latex PRO cuffs are the standard fitment. Alternatively the suit can be fitted with a rubber cuff ring system or the VIKING Bayonet Ring System. Both systems make the fitment of rubber gloves possible.

## FOOTWEAR

The standard boots are an extension of the leg, where a heavy duty flexible rubber outsole is stitched and taped to the end. The outsole features a non slip surface for grip. Alternative boot options are available.

## INCLUDED WITH EACH DELIVERY

Each suit comes supplied with suspenders, carry bag, user manual, repair kit and zip care materials.

## CERTIFICATION & APPROVALS

- EN 14225-2:2005
- BIO approval

Official distributor of Ansell Protective Solutions:



SCANTEK Sp. z o.o.  
81-581 Gdynia, ul. Nowodworcowa 17  
Tel/fax: +48 58 620 83 60 / 58 620 03 04  
kom. +48 501 734 143 / 507 11 0873  
www.scantek.pl, e-mail: info@scantek.pl