



THE WORLDWIDE  
DIVING STANDARD

## VIKING™ PROTECH



VIKING PROTECH with Surveyor hood.

**Flexible drysuit designed for maximum comfort in a wide range of applications, particularly suited to military use. Rear entry design. Vulcanized seams allow for peace of mind when diving under all situations.**

- Internal stitched and taped seams
- External vulcanized seams
- Easy to clean exterior when contaminated
- Easy to repair in the field to minimize downtime
- Extremely flexible and comfortable

### SUIT MATERIAL

Blend of natural and synthetic rubbers (NR/EPDM), on a stretch polyamide/elastane lining.

Total material weight is 1250 g/m<sup>2</sup> ± 100 g/m<sup>2</sup>.

### SEAMS

Internal seams are stitched together with an elastic tape for security. External seams are vulcanized with a 25 mm rubber tape.

### COLOR

All black. Military version has black logos.

### SIZE RANGE

- VIKING Regular: 00/SML, 01/MED, 02/LGE, 03/EXL, 04/XXL, 05/XXXL
- VIKING Wide: 00/SML, 01/MED, 02/LGE, 03/EXL, 04/XXL
- VIKING Double Wide: 00/SML, 01/MED, 02/LGE, 03/EXL, 04/XXL

See the VIKING size chart for detailed size measurements along with boot sizing.

Vulcanized rubber suits are not custom built due to dependency of aluminum mannequins for vulcanization.



THE WORLDWIDE  
DIVING STANDARD

# VIKING™ PROTECH



Internal stitched seam

## REINFORCEMENTS

Additional layers of anti slip textured rubber are applied to areas at risk of wear. The shoulders, zipper and waistband are reinforced. The trouser rear reinforcement extends around the thigh and across to the front of the legs, and down to the boots.

## ZIPPER

A 90 cm long non-magnetic medium duty zipper is placed across the shoulders. A 90 cm non-magnetic HD zipper is fitted to the PROTECH BE NAVY suit version.

## VALVES

Standard configuration includes the following mounted on rubber backing discs:

- Push protected inlet valve, positioned centrally on the chest
- Hose: CEJN fitting, 80 cm long
- Low profile adjustable exhaust valve, placed on the upper left arm

## NECK SEAL

The VIKING PROTECH is fitted with a Surveyor latex neck seal as standard. Option: VIKING Quick Neck collar system, which allows for quick changing of broken seals.

## HOOD OPTIONS

VIKING PROTECH suits may be fitted with a wide range of hood options as follows: Surveyor latex hood + thermal inner hood, Nautic neoprene hood with smooth face seal or Smoothskin hood.

## CUFFS

Latex PRO cuffs are the standard fitment. Alternatively the suit can be fitted with a rubber cuff ring system or the VIKING Bayonet Ring System. Both systems make the fitment of rubber gloves possible.

## FOOTWEAR

The standard boots are 5 mm neoprene lined boots. The outsole features a non slip surface for grip. Alternative boot options are available.

## INCLUDED WITH EACH DELIVERY

Each suit comes supplied with suspenders, carry bag, user manual, repair kit and zip care materials.

## CERTIFICATION & APPROVALS

- EN 14225-2:2005
- BIO approval
- The VIKING PROTECH BE Navy suit, fitted with HD zipper, additionally has HZ chemical approval

Official distributor of Ansell Protective Solutions:



SCANTEK Sp. z o.o.  
81-581 Gdynia, ul. Nowodworcowa 17  
Tel/fax: +48 58 620 83 60 / 58 620 03 04  
kom. +48 501 734 143 / 507 11 0873  
www.scantek.pl, e-mail: info@scantek.pl